

	beamoll 	BeamboxII 	HEXA 	HEXA^{RF} 
Dimensions	710 x 474 x 208 mm	830 x 670 x 250 mm	1110 x 670 x 270 mm	1110 x 811 x 317 mm
Weight	23 kg	48,5 kg	58 kg	72 – 77 kg
Power supply	AC 110-240V	AC 110-240V	AC 110-240V	AC 110-240V
Connection	Wi-Fi / USB / Ethernet	Wi-Fi / USB / Ethernet	Wi-Fi / USB / Ethernet	Wi-Fi / USB / Ethernet
Engraving speed	Max. 750mm/s	Max. 900mm/s	Max. 900mm/s	Max. 2000mm/s
Laser power	30W	55W	60W	30W, 60W lub 80W
Laser source lifespan	Estimated efficiency over 10,000 hours	Estimated efficiency over 10,000 hours	Estimated efficiency over 10,000 hours	Estimated efficiency over 20,000 hours
Tube type	CO2 Glass Diffuser	CO2 Glass Diffuser	CO2 Glass Diffuser	Metal CO2
Engraving resolution	Max. 1000 DPI	Max. 1000 DPI	Max. 1000 DPI	Max. 2000 DPI
Screen	O przekątnej 5"	O przekątnej 7"	O przekątnej 7"	O przekątnej 5"
Tube cooling	Integrated – water-based	Integrated – water-based	Integrated – water-based	Integrated – air-based
Camera	HD 8MP CMOS	HD CMOS	HD CMOS	8MP

